# EKI-2428G-4FA

## 24GE+4G SFP Port L2 Unmanaged Switch with AC Input



#### **Features**

- 24 x Gigabit copper ports + 4 x Gigabit SFP ports
- SFP socket for easy and flexible fiber expansion
- Provides 8K MAC address
- 100~240 V<sub>AC</sub> power input

Introduction

The EKI-2428G is an unmanaged switch with 24 Gigabit ports and 4 Gigabit SFP ports. It is designed for rack-mount installation, and suitable for edge to core industrial networks. The wire speed across all ports up to 56 Gbps for L2 traffic forwarding.

Protection

## **Specifications**

#### **Communications**

oommunioutions			
<ul><li>Standard</li><li>LAN</li></ul>	IEEE 802.3, 802.3u, 802.3x, 802.3ab, 802.3z 10/100/1000BASE-TX, optional 100BASE-FX, 1000BASE-SX/LX/LHX/XD/ZX/EZX	<ul><li> Power Reverse</li><li> Overload Current</li></ul>	Present Present
<ul> <li>Transmission Distance</li> </ul>	Ethernet: Up to 100 m (4- wire Cat.5e, Cat.6 RJ45 cable suggested for Gigabit port) SFP: Up to 110 km (depends on SFP)	Environment <ul> <li>Operating Temperature</li> </ul>	( /
<ul> <li>Transmission Speed</li> </ul>	Gigabit Copper: 10/100/1000 Mbps, Auto-Negotiation Gigabit Fiber: Up to 1000 Mbps	<ul> <li>Storage Temperature</li> <li>Operating Humidity</li> <li>Storage Humidity</li> </ul>	-20 ~ 70°C (-4 ~ 158°F) 10 ~ 95% (non-condensing) 10 ~ 95% (non-condensing)
Interface		<ul> <li>MTBF</li> </ul>	620,427 hours
- Connectors	24 x RJ45 (Ethernet) 4 x SFP (mini-GBIC) ports	Certification	
LED Indicators	10/100T (X): Link/Activity, Duplex/Collision	EMI	CE FCC Class A
	Gigabit Copper: Link/Activity, Speed (1000 Mbps) SFP: Link/Activity	EMS	EN 61000-4-2 EN 61000-4-3
<ul> <li>Debug Port</li> </ul>	RS-232 (RJ45)		EN 61000-4-4
Mechanism			EN 61000-4-5 EN 61000-4-6
<ul> <li>Enclosure</li> </ul>	Metal shell with solid mounting kits		EN 61000-4-8
	442 x 44 x 211.1 mm (17.4" x 1.73" x 8.31")	<ul> <li>Shock</li> </ul>	IEC 60068-2-27
<ul> <li>Mounting</li> </ul>	1U 19" Rack mount	<ul> <li>Freefall</li> </ul>	IEC 60068-2-32
Ū.		<ul> <li>Vibration</li> </ul>	IEC 60068-2-6
Power			
<ul> <li>Power Consumption</li> </ul>	18W		
Barris Land			


• Power Input 100~240V si

100~240V single AC power input

#### AD\ANTECH Industrial Ethernet Solutions

#### All product specifications are subject to change without notice.

### EKI-2428G-4FA



## **Ordering Information**

• EKI-2428G-4FA-AE 24GE+4G SFP Port Unmanaged Ethernet Switch