

## BDC **C-BAND EXT REF 3000X SERIES**

## SPECIFICATIONS

Noise Figure
L.O. Stability
Phase Noise (SSB) max.
Input VSWR
Output VSWR
Gain
Gain Flatness (over full band)
Output P1dB

10 dB max. at room temp. Phase Locked to External Reference Depends on External Reference 2.0:1 max. 2.0:1 max. 40 dB typ., 38 dB min., 42 dB max. ≤4 dB p-p + 5 dBm min.




**Innovative Communication Solutions** 

Via	+ 12V to + 24V DC Feed-Through and Output Connector Output Connector Feed-Through
	300 mA max.
	SMA-Connector (50 Ohm)
	F-Connector (75 Ohm) N-Connector (50 Ohm) SMA-Connector (50 Ohm)
	129 mm x 94 mm x 46 mm (5.07 in x 3.70 in x 1.81 in)
	700 g (24.70 oz)
	- 40 to + 60°C
	- 40 to + 80°C
	10 MHz (sine-wave), -10 to 0 dBm
	Via

## FREQUENCY BANDS

Frequency Band (GHz)	3.40 - 4.20
L.O. Frequency (GHz)	5.15
IF Frequency (MHz)	950 - 1750

## **HOW TO ORDER**



www.norsat.com