



KEY FEATURES

Two Types Touch

Projected Capacitive Multi-touch / Resistive Touch

IP Rating

IP65 Front Panel

Support 3 Signal Interfaces

VGA/DVI/HDMI

Support Modular Extended Display

1 x HDBaseT / 2 x HDBaseT / Wifi Display

Various Mounting Type

VESA Mount 75 / Panel Mount

Advanced Voltage

Support USB Type C

SPECIFICATION

| | | |
|--------------------------|-------------------------|---|
| DISPLAY AND TOUCH SCREEN | Display | 21.5" TFT LCD Monitor Projected Capacitive Multi-touch / Resistive Touch |
| | Max. Resolution | 1920 x 1080 |
| | Brightness | 300 cd/m ² |
| | Contrast | 5000 : 1 |
| | Active Area | 476.64mm x 268.11 (H x V) |
| | Response Time | 25ms |
| | View Angle | 178/178 |
| | Backlight Lifetime | 50,000 Hrs LED Backlight |
| BOTTOM I/O | USB | 1 x USB port (touch to external PC) |
| | Display | 1 x VGA 1 x DVI-D 1 x HDMI |
| | Audio | 1 x Line-in |
| | External Display (opt.) | 1 x HDBaseT 100M / 2 x HDBaseT 100M / Wifi Display |
| POWER | Type | 20V USB Type C VDC Input / 12 to 24 VDC Input with DC Jack |
| ENVIRONMENT | Operating Temperature | 0°C ~ 60°C |
| | Storage Temperature | -20°C ~ 60°C |
| | Relative Humidity | 80% RH@ 50°C, 300Hrs (non-condensing) |
| MECHANISM | IP Rating | IP65 Front Panel |
| | Construction | Aluminum Front Bezel |
| | Dimensions (W x H x D) | TBD |
| | Weight | TBD |
| OTHER | OSD Keypad | Multi-language OSD |
| | Speaker | 2 x 3W |

PACKING LIST

| |
|---------------|
| 1 Monitor |
| 1 Audio Cable |
| 1 VGA Cable |
| 1 USB Cable |
| 1 Quick Guide |