

MVME8100

NXP® QorIQ® P5020 VME64x/VXS SBC

DATA SHEET

- NXP QorIQ P5020 1.8/2.0GHz
- Up to 8 GB DDR3-1333 MHz ECC Memory
- 512 KB FRAM
- 2 PMC/XMC sites
- Embedded NAND Flash (8GB eMMC)
- 2 x 4 PCIe or 2 x 4 SRIO connectivity to VXS backplane P0
- Up to 3 USB 2.0 ports
- Up to 5 Ethernet ports
- Up to 5 Serial ports
- 4 GPIO
- Extended temperature and conduction cooled variants

The SMART Embedded Computing MVME8100 is a high performance 6U VME/VXS SBC featuring the NXP QorIQ P5020 processor supporting high speed DDR3-1333 MHz with ECC. It offers expanded IO and memory features with PCIe and SRIO fabric connectivity and multiple USB, Serial and Ethernet ports. Memory includes up to 8 GB DDR3, 512 K FRAM non-volatile memory, and 8 GB eMMC NAND Flash.

The MVME8100 is offered in commercial and fully rugged variants for extreme environments with extended shock, vibration, temperatures and conduction cooling. It is designed for a range of high end industrial control such as SPE and photo lithography and C4ISR, including Radar/Sonar. It will provide technology insertion to prolong current programs while providing more computing performance and data throughput.

The MVME8100 supports a full range of BSPs including Linux, Wind River VxWorks, and Green Hills Integrity.





Hardware Specifications

PROCESSOR

- NXP QorIQ P5020
- 1.8GHz: ENP4 variant
- 2.0GHz: ENP1 variants

MEMORY

- Designed for 8GB of 64 bit DDR3-1333 ECC SDRAM soldered down
- 16MB SPI ROM for boot code (in 1+1 redundant 8MB banks/devices)
- 512 kB MRAM for data storage
- 8GB NAND Flash with SD/EMMC interface

BACKPLANE I/O

- P0
 - Two SERDES GbE (VITA 41.6) (dedicated)
 - Up to two SRIO x4 links (VITA 41.2)
 - Up to two PCIe x4 links (VITA 41.4); root or end-point
 - One SATA 6 GB
 - Two GPIO
- P1
 - VME64x & 2eSST
- P2
 - PMC1 I/O (64 signals)
 - Two USB 2.0
 - VME64x & 2eSST
 - Four RS232/422/485
 - Two 10/100/1000BaseT Ethernet
 - Two GPIO

OTHER FEATURES

- Real Time Clock with battery backup
- Real time counters
- Watchdog

EXPANSION MODULE

- Site 1 supports PMC or XMC (PCI-X/PCIe x8)
- Site 2 supports PMC or XMC (PCI-X/PCIe x4) or alternatively supports a mounting kit for a 2.5" SATA HDD or SSD A: Contact SMART EC or consult installation/use manual for requirements for rugged (ENP4) SSD modules.

FRONT PANEL CONNECTIVITY

- One GbE (RJ-45)
- One RS232/422/485 console (Micro-BD9)
- One USB 2.0 (Type A)

POWER REQUIREMENTS

- ENP1: 38 W idle, 42 W typical, 54 W max
- ENP4: 65 W @ 85 °C card edge

Software and Firmware Specifications

BOOT

- UBoot binary and source code

BOARD SUPPORT PACKAGES

- VxWorks available through Wind River
- Linux





Estimated MTBF

MTBF estimated per Telcordia SR-332, issue 2, ground fixed, controlled environment, unit ambient air temperature of 40 °C is 564,000 hours (ENP1 version), 577,000 hours (ENP4 version) at 60% confidence level. Contact SMART EC for alternative environments or temperatures.

All Modules

ENVIRONMENTAL

Ruggedization Level 3	ENP1	ENP4
Cooling Method	Forced Air	Conduction
Operating Temperature	0 °C to +55 °C	-40 °C to +85 °C
Storage Temperature	-40 °C to +85 °C	-55 °C to +105 °C ³
Vibration Sine (10min/axis)	2G, 5 - 500 Hz	10G, 15 to 2000 Hz
Vibration Random (1hr/axis)	.002 g ² /Hz, 15 to 2000 Hz ¹	0.1 g ² /Hz, 15 to 2000 Hz (12 GRMS) ²
Shock	20 g/11 mS	40 g/11 mS
Humidity	to 95% RH	to 100% RH
Conformal Coating	No	Acrylic

Note 1: Flat 15-1000 Hz, -6 db/octave 1000 Hz – 2000 Hz [MIL-STD 810F Figure 514.5C-17]

Note 2: +3 db/octave 15-300 Hz, Flat .1g² 300-1000Hz, -6 db/octave 1000 Hz – 2000 Hz [MIL-STD 810F Figure 514.5C-8]

Note 3: ENP4 storage temperatures exceed NAND flash limits of -40° to -85°C. Data degradation can occur.

RoHS (reduction of hazardous substances) status— ENP1: RoHS II, ENP4: RoHS 5/6 lead solder

ELECTROMAGNETIC COMPATIBILITY (EMC)

- SMART EC board products are tested in a representative system to the following standards:
 - U.S.: FCC Part 15, Subpart B, Class A (non-residential)
 - Canada: ICES-003, Class A (non-residential)
 - CE Mark per European EMC Directive 2004/108/EC with Amendments; Emissions: EN55022 Class A; Immunity: EN55024
 - KCC Mark (ENP1)

DOCUMENTATION

- Installation and Use Manuals
- Programmers Reference Manual
- Release Notes
- OS Release Notes and User Guide





Ordering Information	
Part Number	Description
Boards	
MVME8100-202200401E	P05020 2.0GHz, 4GB DDR3, 2PMC/XMC, ENP1 IEEE
MVME8100-04CC	P05020 1.8GHz, 4GB DDR3, 2PMC/XMC, ENP4, conformal coated
Accessories	
SERIAL-MINI-D2	Serial cable - Micro D sub connector to standard DB-9
ACC/CABLE/SER/DTE/6E	Serial cable, RD 009, 2M, 2 DTE MD/D, RJ45 to DB9

SOLUTION SERVICES

SMART Embedded Computing provides a portfolio of solution services optimized to meet your needs throughout the product lifecycle. Design services help speed time-to-market. Deployment services include worldwide technical support. Renewal services enable product longevity and technology refresh.

CONTACT DETAILS

+1 602-438-5720

Info@smartembedded.com

www.smartembedded.com/ec/contact

The stylized "S" and "SMART", and the stylized "S" combined with "SMART" and "Embedded Computing" are trademarks of SMART Modular Technologies, Inc. NXP and QorIQ are trademarks of NXP B.V. All other trademarks and registered trademarks are the property of their respective companies. ©2019 SMART Embedded Computing, Inc. Specifications are subject to change without notice. All rights reserved. For full legal terms and conditions, please visit www.smartembedded.com/ec/legal

